

3 Jaw Lathe Chucks Direct Mount



Features:

- Semi-steel body
- D-1 series short taper spindle with camlock nose
- Complete with chuck key

Stock No.	Specification
1055-0063	6" D1-3,Thru Hole: 1.575" (K11160A/D3)
1055-0064	6" D1-4,Thru Hole: 1.575" (K11160A/D4)
1055-0065	6" D1-5,Thru Hole: 1.575" (K11160A/D5)
1055-0084	8" D1-4,Thru Hole: 1.969" (K11200A/D4)
1055-0085	8" D1-5,Thru Hole: 1.969" (K11200A/D5)
1055-0086	8" D1-6,Thru Hole: 1.969" (K11200A/D6)
1055-0105	10" D1-5,Thru Hole: 2.756" (K11250A/D5)
1055-0106	10" D1-6,Thru Hole: 2.756" (K11250A/D6)
1055-0108	10" D1-8,Thru Hole: 2.756" (K11250A/D8)
1055-1211	12" D1-11,Thru Hole: 3.937" (K11325A/D11)
1055-1206	12" D1-6,Thru Hole: 3.937" (K11325A/D6)
1055-1208	12" D1-8,Thru Hole: 3.937" (K11325A/D8)
1055-1508	15" D1-8,Thru Hole: 5.11" (K11380A/D8)
1055-1611	16" D1-11,Thru Hole: 5.11" (K11400A/D11)
1055-1603	160mm, D1-3,Thru Hole: 40mm (K11160A/D3)
1055-1604	160mm, D1-4,Thru Hole: 40mm (K11160A/D4)
1055-1605	160mm, D1-5,Thru Hole: 40mm (K11160A/D5)
1055-2004	200mm, D1-4,Thru Hole: 50mm (K11200A/D4)
1055-2005	200mm, D1-5,Thru Hole: 50mm (K11200A/D5)
1055-2006	200mm, D1-6,Thru Hole: 50mm (K11200A/D6)
1055-2505	250mm D1-5,Thru Hole: 70mm (K11250A/D5)
1055-2506	250mm, D1-6,Thru Hole: 70mm (K11250A/D6)
1055-2508	250mm, D1-8,Thru Hole: 80mm (K11250A/D8)
1055-3256	325mm, D1-6,Thru Hole:100mm (K11325A/D6)
1055-1511	15" D1-11,Thru Hole: 5.11" (K11380A/D11)
1055-3208	325mm, D1-8,Thru Hole:100mm (K11325A/D8)
1055-3211	325mm, D1-11,Thru Hole:100mm (K11325A/D11)
1055-0380	380mm, D1-8,Thru Hole: 100mm (K11380A/D8)
1055-0381	380mm, D1-11,Thru Hole: 100mm (K11380A/D11)

HITECH(Qingdao)
ENTERPRISES INC