



Stock No. Description

TB-1018. . . .	OD:4mm, L:18" (457. 20mm)
TB-1024. . . .	OD:4mm, L:24" (609. 6mm)
TB-1036. . . .	OD:4mm, L:36" (914. 40mm)
TB-2028. . . .	OD:6mm, L:18" (457. 20mm)
TB-2024. . . .	OD:6mm, L:24" (609. 6mm)
TB-2036. . . .	OD:6mm, L:36" (914. 40mm)
TB-3024. . . .	OD:8mm, L:24" (609. 6mm)
TB-3036. . . .	OD:8mm, L:36" (914. 40mm)

## TB-1018...3036

It is a Fiber-optic endoscope with unique brightness adjustment function to provide more convenient operation.

### Features :

Features	Dia 4mm/6mm	Dia 8mm
Cable Material	PE	Stainless with PVC coating
Minimum Articulation	R40mm	
Working Length	45-500(cm)	
Lamp	2.8V 0.5A	
Power	2-AA Batteries	
Field of View	55°	
Focus	20mm to infinity (fixed focus point)	
View directon	Front	
Waterproof	Objective lens and fibre tube is waterproof under 1013hpa,Eyepiece is un-waterproof	
Working Temperature	-20°- 80°	

